



See nothing, hear everything

The CCM662 is a true high performance ceiling-mount speaker. The tweeter has a 25mm(1in) aluminium dome tweeter and its housing pivots for adjustable off-axis treble response. The die-cast chassis of the bass/midrange driver provides extra rigidity which results in a cleaner, faster bass and a three-position EQ switch offers a better off-axis response. With superior cross-over components along with gold plated terminals the CCM662 has an impressive maximum amp power of 150W. Its blue aramid fiber cone means that the unit is well hidden behind the grille but still produces a remarkably clear and dynamic sound. Incorporating QuickDogs™ and plug-and-play functionality it is quick and easy to install.

Technical Specifications

Description	2-way in-ceiling system
Drive Units	1x ø25mm (1in) Nautilus™ swirl loaded aluminium dome tweeter 1x ø150mm (6in) blue aramid fiber cone bass/midrange
Frequency Range (-6dB)	45Hz – 50kHz
Recommended Amp Power	25 – 150w
Sensitivity SPL (2.83V, 1m)	88dB
Impedance Nominal (min)	8Ω (4.5Ω)
Frame diameter	240mm (9.5in)
Cut-out diameter	202mm (8in)
Depth behind surface	133mm (5.2in)
Protrusion	4mm (0.2in)
Pre-mount Kit	C6
Back Box	6C

