

Proyector láser Solid Shine LCD de 16.000 lúmenes

PT-MZ16KL

Proyector con fuente de luz láser, 3 LCD, 16.000 lúmenes, WUXGA



KEY FEATURES

- 3 LCD láser, 16.000 lúmenes, WUXGA
- Su diseño silencioso (38 dB en modo normal) y ligero (22 kg) es ideal para salas de conferencias y seminarios
- 20.000 horas de funcionamiento sin necesidad de mantenimiento gracias a su diseño resistente a la entrada de polvo y al filtro ecológico de larga duración
- El motor de triple accionamiento garantiza un funcionamiento ininterrumpido con una función de conmutación por error. Una entrada de señal auxiliar secundaria y la función de supervisión reducen la importancia de posibles fallos técnicos.
- Instalación flexible con posibilidad de elegir entre siete objetivos con zoom opcionales. Configuración sencilla con el software Geo Pro y la función DIGITAL LINK

La serie MZ16 es la gama de proyectores LCD más silenciosa y potente de Panasonic para el sector de la enseñanza y la empresa, diseñada para una configuración simplificada y un funcionamiento sin necesidad de mantenimiento que reduce la carga de trabajo para el director audiovisual.

Este flexible y rentable proyector láser SOLID SHINE™ ofrece un brillo de hasta 16 000 lúmenes (PT-MZ16K) y resolución WUXGA para una proyección de alta calidad, con funcionamiento silencioso (38 dB en modo normal) y diseño ligero (22 kg). Acepta una señal de entrada de 4K/60p, que se convierte a la resolución del proyector (1920 x 1200).



SPECIFICATIONS

Projector type	LCD projectors
DLP™ chip Number of Pixels	2,304,000 (Pixels 1920 x 1200) pixels x 3
Light Source	Laser diodes
Light output*1	16,000 lm
Time until light output declines to 50 %*2	20,000 hours (NORMAL)
Resolución	1920 x 1200 pixels
Lens	Optional powered zoom lenses
Lens shift Vertical (from center of screen)	±60 % (±40 % with ET-EMW200, ±50 % with ET-EMW300) (powered)
Lens shift Horizontal (from center of screen)	±20 % (±19 % with ET-EMW200) (powered)
Keystone Correction Range	Vertical: ±40° (±14° with ET-EMW200/ET-EMW300, ±22° with ET-EMW400/ET-EMW500), Horizontal: ±15° (±8° with ET-EMW200/ET-EMW300)
Keystone correction range with optional ET-UK20 Upgrade Kit	Vertical: ±40° (±14° with ET-EMW200/ET-EMW300, ±22° with ET-EMW400/ET-EMW500), Horizontal: ±40° (±8° with ET-EMW200/ET-EMW300, ±15° with ET-EMW400/ET-EMW500)When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55°.
Instalación	Ceiling/floor, front/rear, free 360-degree installation
Terminals SDI In	BNC x 1: 3G/HD-SDI input
Terminals HDMI In	HDMI 19-pin x 1 (Compatible with HDCP 2.2, Deep Color, 4K/60p signal input*3)
Terminals DVI-D In	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
Terminals Remote 2 In	M3 x 1 for wired remote control
Terminals LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PjLink™ [Class 2], Art-Net)
Power Supply	AC 100-240 V, 50/60 Hz
Power Consumption	1,050 W
Cabinet Materials	Molded plastic
Operation noise*1	38 dB (NORMAL) / 32 dB (Quiet)
Operating Environment	Operating temperature: 0–45 °C (32–113 °F)*6; Operating humidity: 10–80 % (no condensation)
Applicable Software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro (ET-UK20 Upgrade Kit, ET-CUK10 Auto Screen Adjustment Kit), Smart Projector Control for iOS/Android™
Note	*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. *2 Around this time, light output will have decreased by approximately 50%. IEC62087: 2008 Broadcastcontents, NORMAL Mode, Dynamic Contrast [2], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m3 of particulate matter. Estimated time until light output declines to 50 % varies depending on environment. *3 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI®. *4 With legs at shortest position. *5 Average value. May differ depending on the actual unit. *6 When using the projector at an altitude lower than 2,700 m (8,858 ft) above sea level, and the operating environment temperature becomes 35 °C (95 °F) or higher, the light output may be reduced to protect the projector.
Terminals REMOTE 1 IN	D-sub 9-pin (female) x 1 for external control (parallel)
Contrast Ratio*1	3,000,000:1 (Full On/Full Off) * With [Dynamic Contrast] set to [3]
Center-to-corner zone ratio*1	85 %
Filter	Included (Estimated maintenance time: approx. 20,000 hours)
Terminal RGB In	D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Dimensions (W x H x D)	650 x 211*4 x 440 mm (25 19/32" x 8 5/16"*4 x 17 21/64") (Without lens)
Terminals DC Out	USB Connector (Type A) x 1 (Output 5 V/2 A)

DLP™ Chip Panel Size	25.4 mm (1.0 in) diagonal (16:10 aspect ratio)
Terminals DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PJLink™ [Class 2], Art-Net, HDCP 2.2, Deep Color, 4K/60p signal input*3)
Terminals Serial/Multi Projector Sync In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals Serial/Multi Projector Sync Out	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
Weight*5	Approx. 22.3 kg (49.2 lbs)
Screen size [diagonal]	2.03–12.7 m (80–500 in), 16:10 aspect ratio
Terminals Remote 2 Out	M3 x 1 for link control (for wired remote control)

URL: <https://business.panasonic.es/sistemas-visuales/pt-mz16kl>

CONTACT

Web: <https://business.panasonic.es/sistemas-visuales/contact-us>