

# PRO-7800-S-THX



## THX® ULTRA2 CERTIFIED

Works well with multi-channel movie and music presentations playing up to reference levels in rooms of 3,000 cubic feet or larger.

## CINEMA QUALITY SOUND

Employs an 8-inch aluminum woofer and a patent-pending horn array, consisting of two vertically-stacked Tractrix Horn-loaded tweeters.

## WIDE DISPERSION SURROUND TECHNOLOGY (WDST)

In order to create enveloping sound fields and precise localization of individual effects, this speaker also utilizes Klipsch's Wide Dispersion Surround Technology™. Also referred to as WDST, this no-compromise approach gives much more placement flexibility than conventional designs.

## MAXIMUM INSTALLATION RELIABILITY

This in-wall speaker also consistently delivers thrilling, realistic sound, whether it's installed horizontally or vertically. It features sure-grip mounting dogs that provide even pressure against drywall for long-term installation reliability, and includes a paintable grille that blends in perfectly with any décor.

## UNLIMITED FLEXIBILITY

Timbre matched to all of our THX-certified products, so you can mix and match to create an unbeatable, discreet stereo or home theater system that's just right for you.

## EDGE-TO-EDGE GRILL

Covering the whole of the speaker makes painting the product both simpler and quicker. Premium Neodymium magnets make it easy to install and remove and ensure a secure and flush fit without any moving parts. The flat grill allows better harmonization with today's modern interior designs and disappear into the background, enabling sound to take center stage.

## SEAMLESS HIGH PERFORMANCE

The Klipsch Professional Series introduces a new line of high-performance architectural speakers unlike any you've heard before. Superior acoustic technology makes the Professional Series the most dynamic, powerful, direct-radiating speakers available.

## SPECIFICATIONS

SYSTEM	2-way In-wall
FREQUENCY RESPONSE	80Hz-20kHz +/- 3dB
POWER HANDLING (Cont/Peak)	100W/400W
SENSITIVITY	90dB
IMPEDANCE	8 Ohms
CROSSOVER FREQUENCY	2130Hz
HIGH FREQUENCY DRIVER	Two 1" (2.5cm) Titanium dome neodymium tweeters in a diffuse Tractrix® horn array
LOW FREQUENCY DRIVER	8" (20cm) Aluminum Cone Woofer
ENCLOSURE TYPE	Sealed Enclosure
HOLE DIMENSION	19" (48.3cm) H x 10" (25.4cm) W
DIMENSIONS	20.8" (52.7cm) H x 11.8" (29.8cm) W
MOUNTING DEPTH	3.7" (9.4cm)
WEIGHT	17.5 lbs. (7.9kg)
FINISH	White with Brushed Aluminum Facia